

## HTML <command/> Tag

#command# description, syntax, usage, attributes and examples HTML-5.com is a great guide for web developers. [TV Series & Actors and Actresses](#). Follow [TV Series](#) and [HTML 5](#) on Google+.

[HTML-5.com](#) > [itemscopehttp://data-vocabulary.org/Breadcrumb<span itemprop="title">HTML 5</span>](#) > [itemscopehttp://data-vocabulary.org/Breadcrumb<span itemprop="title">HTML Tags</span>](#) > [itemscopehttp://data-vocabulary.org/Breadcrumb](#)  
[HTML <command/> Tag](#)

> [itemscopehttp://data-vocabulary.org/Breadcrumb<span itemprop="title">Examples</span>](#)

---

### The <command/> Tag in HTML 5

The <command> tag is one of the [tags for interactive content in HTML](#).

[back to top](#)

---

### <command/> Tag Syntax

Rules for coding HTML `command/` elements

```
<code mode="pre"><command .../></code>
```

### <command/> Content Model

#### Contents of the command element

Content: *Empty*. All properties are coded using [attributes](#).

Since the `<command/>` tag is a [void element](#), it is not allowed to have any content, even [HTML comments](#) and therefore should always be coded as a self-closing [standalone tag](#), ending with the delimiters `/>` rather than just `>` (`<command .../>`).

[back to top](#)

---

### <command/> Tag Attributes

#### Attributes of the <command/> tag

<a href="#">global attributes</a>	In addition to the personal attributes of the <command> tag below, any of the <a href="#">common HTML attributes</a> can also be coded.
checked="checked"	
disabled="disabled"	
icon	a <a href="#">URI reference</a> that resolves to the <a href="#">URL</a> of a small two-dimensional image resource  Use <a href="#">percent escape codes</a> as explained in the <a href="#">URL-encoding tutorial</a> for any special characters in the <a href="#">URI reference</a> .

	<p>If the value of the <code>icon</code> attribute resolves to an <a href="#">HTTP URL</a>, it may contain any of the following components:</p> <ol style="list-style-type: none"> <li>1. protocol scheme, typically <code>http:</code> or else <code>https:</code></li> <li>2. username, followed by an "@"</li> <li>3. host name or <a href="#">IP</a> address</li> <li>4. port number, which defaults to 80 for the <code>http</code> scheme and 443 for the <code>https</code> scheme</li> <li>5. absolute or relative path</li> <li>6. search query, indicated by "?"</li> </ol> <p>If the protocol scheme, username, host name/IP address and port number are omitted the default is the current host - the same server as the base of the current document. If the path starts with a slash <code>/...</code>, it is an absolute path from the document root directory (<a href="#">AKA</a> "<code>&lt;dfn&gt;web root&lt;/dfn&gt;</code>") on the server. A relative path will be resolved relative to the base of the current document.</p>
label	
radiogroup	
title	Although <code>title</code> is one of the common attributes, which can be coded on any HTML element, it performs somewhat differently when coded on the <code>command</code> tag.
<pre>type="command" type="checkbox" type="radio"</pre>	

[back to top](#)

## <command/> Tag Examples

Examples of the `command` element in HTML 5

[back to top](#)

## Changes in HTML 5 - <command/> Tag

### What's new in HTML 5

The `<command>` tag is one of the new elements in HTML 5.

## Differences between HTML 5 and earlier versions of HTML

The <command> tag did not exist in older versions of HTML.

The [2000-2010 Recommendations from the W3C HTML Working Group](#) defined the [HTML namespace](#) for the names of all [HTML element types](#), which now includes the **command** element name. In older (pre-2000) [versions of HTML](#), element type names were not associated with a namespace.

[back to top](#)

---

*THE END*